

**UD Series****UDL Series****UDE/UDR Series****UDK Series****FEATURE:**

Constant Voltage Mode
Super Mini Size and Easy Portable
Light & Convenient Plug In
Wall Mount Type

APPLICATION:

Lithium Ion Battery Charger
Digital Camera
CD-ROM & HUB
Communication Terminals
Wireless LAN Station
External Hard Disk
Portable Device Or Machine

INPUT/OUTPUT SPECIFICATIONS:

Input Voltage: (UD103 & UDL103): AC100V-120V, (UD303 & UDx303, x = E, K, L & R): AC100V-240V, 50/60Hz
Output Power: 3.5W
Output Voltage: See table below
Over Current Protection: 120% Min
Over Voltage Protection: 120% Min
Short Protection: Auto Recovery
Load Regulation: $\pm 5\%$

GENERAL SPECIFICATIONS:

Operating Temperature: 0 ~ 40°C
Operating Relative Humidity: 5 ~ 95%RH
Storage Temperature: -20 ~ 65°C
Withstanding Voltage: (UD103 & UDL103): AC 2000V/Min (between Input & Output), 10mA Max
(UD303 & UDx303, x = E, K, L & R): AC 3000V/Min (between Input & Output), 10mA Max
Insulation Resistance: DC 500V 100M Ω (Min.) (between Input & Output)
Efficiency: 65% Min

Model Series	UD103	UD303	UDL303	UDE303	UDR303	UDK303
	UDL103					
AC Input Rating	90V~132V	90V~264V				
DC Output Rating	3V~24V Max 1A Max					
Safety						

