



Safety , Efficient & Earth friendly

Dual Output Switching Power Adaptor 25W Series Dual Output

UEA&UEB&UEC Series



Product

- ✓ Stability
- ✓ Compact size
- ✓ Available at IEC C6, C8 & C14 inlet type
- ✓ Suit external HDD, computer peripheral etc

Protection:

- ✓ Short circuit protection
- ✓ Over Voltage Protection
- ✓ Over Current Protection

Efficiency:

- ✓ CEC Leve 5
- ✓ Energy Star 2.0

Safety Approvals:

- ✓ UL60950
- ✓ CAN/CSA C22.2 NO. 60950
- ✓ CE (Low Voltage Directive)
- ✓ AS/NZS 60950.1
- ✓ PSE
- ✓ GB4943-2001
- ✓ GOST
- ✓ K60950
- ✓ IEC 60950

Emissions:

- ✓ CE CISPR 22 Class B
- ✓ VCCI Class B
- ✓ GB9254-2008/GB17625.1-2003

Immunity:

- ✓ EN55024/A1:2001
- ✓ Electrostatic discharge: 61000-4-2
- ✓ Radiated electromagnetic fields:61000-4-3
- ✓ Fast transients (Burst): 61000-4-4
- ✓ Surge transients: 61000-4-5
- ✓ Conducted disturbance: 61000-4-6
- ✓ Voltage dips, interruptions & Variations:61000-4-11

Electrical Spec:

Absolute Maximum Rating

| Input | | | | | |
|-------------|-----|---------|-----|-------|-----------------------------|
| Description | Min | Typ | Max | Units | Comment |
| Voltage | 90 | 120/240 | 264 | VAC | 2 Wire No Protection Ground |
| Frequency | 47 | 50/60 | 63 | Hz | |

| Environmental | | | | | |
|--------------------------|-----|-----|-----|-------|---------------------------|
| Description | Min | Typ | Max | Units | Comment |
| Operating Temperature | 0 | - | 40 | °C | Free Convection,Sea level |
| Non-Operating Temperture | -20 | - | 65 | °C | Free Convection,Sea level |
| Operating Humidity | 10 | - | 90 | %RH | No Condensing |
| Non-Operating Humidity | 10 | - | 90 | %RH | No Condensing |

Typical model list:

Dual Output Switching Power Adaptor 25W Series Dual Output

| Input Condition | | DC Output Voltage | DC Output Current | Output Voltage Precision | Ripple & Noises | Regulation | | Option/Remark |
|-------------------------------------------------------|---|-------------------|-------------------|--------------------------|-----------------|------------|------|---------------|
| | | | | | | Line | Load | |
| Input Voltage: 90V-264Vac Frequency: 47-63Hz | 1 | 5V | 1.5A | ±5% | 50mV | ±1% | ±5% | |
| | | 12V | 1.5A | ±5% | 120mV | ±1% | ±5% | |
| | 2 | 5V | 1.5A | ±5% | 50mV | ±1% | ±5% | |
| | | 12V | 1.0A | ±5% | 120mV | ±1% | ±5% | |
| | 3 | 5V | 2.0A | ±5% | 50mV | ±1% | ±5% | |
| | | 12V | 1.5A | ±5% | 120mV | ±1% | ±5% | |
| | 4 | 5V | 2.0A | ±5% | 50mV | ±1% | ±5% | |
| | | 12V | 1.0A | ±5% | 120mV | ±1% | ±5% | |
| | 5 | - | - | - | - | - | - | - |

Measurement condition

1. Measurements shall be made with an oscilloscope with 20MHz bandwidth.

2. Outputs shall be bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.

Mechanical

| UEA125D Series | UEA325D Series | UEB325D Series | UEC325D Series |
|----------------------------------------------------------|--------------------------------------------------------------------------------------|----------------|----------------|
| | | | |
| CB (The CB meets both IEC60065 & IEC60950 standards) | (Only 5V/1.5A, 12V/1.5A) CB (The CB meets both IEC60065 & IEC60950 standards) | | |

Packing Spec:

| Type | Pcsper Carton | Gross Weight (kg) | Net Weihgt(kg) | Size(mm) | CBM(m2) | Container | Ctn/Contai ner | Pcs/Contai ner | Gross Weingt (Ton) | Remark |
|---------|---------------|-------------------|----------------|-------------|---------|-----------|----------------|----------------|--------------------|---------------|
| UEA125D | 32 | 9.82 | 8.32 | 406x250x298 | 1x1.2 | 20 | 800 | 25600 | 8096 | With Gift Box |
| UEA325D | 50 | 16 | 13 | 565x393x255 | 1x1.2 | 20 | 400 | 20000 | 6640 | Bulk package |
| UEB325D | 32 | 9.82 | 8.32 | 406x250x298 | 1x1.2 | 20 | 800 | 25600 | 8096 | With Gift Box |
| | 50 | 16 | 13 | 565x393x255 | 1x1.2 | 20 | 400 | 20000 | 6640 | Bulk package |
| UEC325D | 32 | 9.82 | 8.32 | 406x250x298 | 1x1.2 | 20 | 800 | 25600 | 8096 | With Gift Box |
| | 50 | 16 | 13 | 565x393x255 | 1x1.2 | 20 | 400 | 20000 | 6640 | Bulk package |